

Wallberry - Epoxy Grout

Wallberry Epoxy Grout (Three Components & Two part Gel Epoxy)

► Description :

Wallberry Epoxy Grout is a Epoxy based adhesive. It is easily applicable in the joints of vitrified tiles, glass mosaic tiles and other tiles. Also, it is suitable for the joints of granite, natural stone, composite marble and quartz stone. The excellent feature of Wallberry Epoxy Grout is that, it can easily be cleaned and surface with water and scrubber/scotch brite within stipulated time.

► Advantages :

- Easy to install and clean
- Cleanable with water
- Colour fast
- Non cracking and powdering
- Hard and durable joints
- Hygienic and chemical resistant
- Waterproof and durable finish
- Stain free
- Temperature resistant
- High strength and versatile

► Area of Application :

- Wallberry grout is ideally suited for residential and commercial installation where the materials must resist physical abuse, stains, spillage, and chemical attack.
- Wallberry grout is applied in grooves of tiles used in kitchens, bathrooms, swimming pools, fountains, hospitals, operation theaters, sterilization rooms, restaurants, cafeterias, and high traffic areas.

► Method of application :

a) Ratio of epoxy kit : For Three Component

For 1 kg.: resin (200gm), hardener (100gm) & filler (700gm)

For 5 kg.: resin (1kg.) hardener (500gm) & filler (3.5 kg.)

b) Ratio of epoxy kit : For Two part Gel Epoxy

For 1 kg.: resin (666 GM), hardener (333gm)

For 5 kg.: resin (3330gm.) hardener (1665gm)

c) Tools for application :

- Paint brush to clean joints
- Scrubber / scotch brite
- Shallow pan
- Soap solution
- Rubber trowels of 4" x 6" size
- bucket full with water

► Coverage :

Theoretical coverage for calculation

(Tile length + tile breadth)x(tile thickness x specific gravity*)

.....kg/m²

(Tile length+joint width) x (tile breadth+joint width)

-*Specific gravity=1.70

- All the dimensions are in mm.

Note : it may vary with tile size, groove width and groove depth.

► Colours :

Available in selected range of colours

(light, Dark & fluorescent refer shade card)

► Packing : 1 kg. & 5kg.

kit	1 kg.	5kg
resin	200gram	1kg.
hardener	100gram	500gram
filler	700gram	3.5kg.

